



RESIDENTIAL • COMMERCIAL • INDUSTRIAL

FLOORSAFE
FLOORSAFE (AUCKLAND) LIMITED

Anti-Slip Solutions - Slippery surfaces made Safe!

2/11 Bermuda Road
St Heliers
Auckland 1071
New Zealand

Phone: (09) 575-7500
Mobile: (027) 506-7785
email: info@floorsafe.net.nz
Web www.floorsafe.net.nz

FLOORSAFE STAIR NOSINGS

September 2008

- R-CC** 10um anodised aluminium 25mm x 63mm
Weight 0.621kg/m. Alloy Temper 6063/T5
Inserts 42mm self adhesive rubber/cork 2.5mm thick
- R-NA** 10um anodised aluminium. 37mm x 75mm
Weight 0.770kg/m. Alloy Temper 6063/T5
Inserts 51mm rubber.
- R-KZ** 10um Anodised Aluminium with bull nose edge 37mm x 80mm
Weight 0.694kg/m. Alloy Temper 6063/T5
- R-CF** 10um anodised aluminium. 37mm x 71mm
Weight 0.710kg/m. Alloy Temper 6063/T5
Inserts 51mm Rubber
- R-NAC** 10um anodised aluminium. 37mm x 75mm
Weight 0.815kg/m. Alloy Temper 6063/T5
Inserts 51mm rubber.
- R-MN** 1.6mm Galvanised metal angle coated with a 2-part polyurethane coating.
The coating is of the highest quality, hard wearing & exceeds the recommendations of HB-197. This nosing also achieves a classification of V according to table 2 AS/NZS 4586:2004

**Floorsafe products are available throughout
Australia, New Zealand, Malaysia, Brunei, Thailand, Japan & Hong Kong.**